

Looking for the most competitive product?

Flex6000



Bitel

9F Yohyun B/D 242-29, Nonhyun-Dong, Gangnam-Gu, Seoul, 135-830, KOREA
TEL:82-2-545-2630 FAX:82-2-545-0190
<http://www.bitelpos.com> E-mail:bitel@bitelpos.com



Specification of Flex6000

Model	Flex6000
CPU	Mips 32bits processor, Clocked 96Mhz With cryptography engine, MMU support
Flash Program/Data ROM	8MB Program Down Loadable Flash ROM.
RAM	2MB SRAM with battery backup
LCD	Graphics LCD Display 128 × 64 Dots.(16character*4Lines) LED Back Light.
PIEZO BUZZER	Used PWM Generator.
BATTERY	Lithium Battery For Real time clock
RS-232	Up to 460,800bps. One General Purpose Serial Port
MSR	ISO 7811 Track 1&2 (2&3 is Option)
SECURITY	Fully support 3DES standard Master/Session and DUKPT key management method (Meet ISO and ANSI standard for PIN encryption, KEY management, MAC such as ANSI X9.8,ANSI X9.24,ANSI X9.19, ISO9564, ISO11568, ISO13491 and etc) DES, 3DES, RSA, AES and other algorithms support
POWER SUPPLY	5V or 12V DC power input option with RS 232 signal level output
IC CARD	Smart card with two SAM interface EMV L1/L2 V4.0 compliant