

Flex5100

Wireless, Simply the best!



GSM/GPRS, CDMA



11F Yohyun B/D 242-29, Nonhyun-Dong, Gangnam-Gu, Seoul, 135-830, KOREA
 TEL:82-2-545-2630 FAX:82-2-545-0190
<http://www.bitelpos.com> E-mail:bitel@bitelpos.com



Specification of Flex5100

MODEL	Flex5100 (Wireless)
CPU	Mips 32bits Clocked at 96Mhz
FLASH	8MB Flash Program ROM
SDRAM	16MB of working RAM (Option)
SRAM	2MB SRAM with battery backup
RTC	Real time Clock (Battery Operated)
LCD	Graphics LCD Display 128x64 Dots / Icon display
PIEZO BUZZER	Used PWM Generator (Various Sound Selection)
BATTERY	Lithium Ion Battery (8.4V)
MODEM	GSM / GPRS modem or CDMA modem module
RS-232/USB	Up to 460,800bps Serial Port/USB
MSR	ISO 7811 Track 1&2 (2&3 is Option)
PRINTER	Thermal Line Printing Number of Dots 384 Dots Resolution 8 Dots/mm Printing Speed 75mm/s
A/D Converter	Internal 6 Channel A/D
IC CARD	Smart card with 2SAM socket
POWER SUPPLY	85 to Volt AC 50/60Hz SMPS Free Voltage AC Adapter