

IC5100

Looking for the most competitive product?



GSM/GPRS, CDMA

Bitel

9F Yohyun B/D 242-29, Nonhyun-Dong, Gangnam-Gu, Seoul, 135-830, KOREA
TEL:82-2-545-2630 FAX:82-2-545-0190
<http://www.bitelpos.com> E-mail:bitel@bitelpos.com

Specifications of IC5100

| | |
|----------------------|---|
| MODEL | IC 5100 (Wireless) |
| CPU | Mips 32bits Clocked at 96Mhz |
| FLASH | 8MB Flash Program ROM |
| SDRAM | 16MB of working RAM (Option) |
| SRAM | 2MB SRAM with battery backup |
| RTC | Real time Clock (Battery Operated) |
| LCD | Graphics LCD Display 128x64 Dots / Icon display |
| PIEZO BUZZER | Used PWM Generator (Various Sound Selection) |
| BATTERY | Lithium Ion Battery (7.2V) |
| MODEM | GSM / GPRS modem or CDMA modem module |
| USB/RS-232 | USB2.0/ Up to 460,800bps (One General Purpose Serial Port) |
| MSR | ISO 7811 Track 1&2 (2&3 is Option) |
| PRINTER | Thermal Line Printing Number of Dots 384 Dots Resolution 8 Dots/mm Printing Speed 75mm/s |
| A/D Converter | Internal 6 Channel A/D |
| IC CARD | Smart card with 2SAM socket |
| POWER SUPPLY | 85 to Volt AC 50/60Hz SMPS Free Voltage AC Adapter |